

# Boyd's Speedway Rules

Official copies of Track Rules will be available at the Track.  
The Rules printed here are for information only.

## B-HOBBY

1. CAR & BODY
  - A. 1973 cars or newer
  - B. 108" minimum wheelbase
  - C. Stock steel bodies only
  - D. Hulling is allowed but must retain stock firewall and floor pan
  - E. All doors must be welded shut
  - F. 6" spoiler. 12" long side braces no higher than spoiler
  
2. ENGINE
  - A. Any cubic inch
  - B. Any intake and carburetor allowed
  - C. Headers permitted
  - D. No angle plug or aluminum heads
  - E. OEM ignition only
  - F. INTERNAL COMPONENTS MUST BE STOCK **(NO EXCEPTIONS)**
  
3. SUSPENSION
  - A. Springs and shocks must remain in stock location
  - B. No wedge bolts or adjustable spring cups
  - C. All A-frames and control arms must remain stock (may be lengthened or shortened)
  - D. All steering components must remain stock
  - E. Stock-type rear-ends only (may be locked)
  - F. No traction-aiding devices allowed (90/10 shock, pull bars, lift bars, etc.)
  
4. TRANSMISSION
  - A. No aftermarket or direct-drive transmission

5. ROLL CAGE

- A. Must have at least main loop with braces running front and rear
- B. If driver's door is hulled, you must run at least three (3) bars in it
- C. Full roll cages are recommended

6. WEIGHT

- A. 3,100 pounds minimum at any time

7. FUEL CELL

- A. Fuel cells are mandatory
- B. Must be in 20-gauge steel containers and securely fastened

8. TIRES & WHEELS

- A. Any legal Hoosier 55 or American Racer 56
- B. Steel wheels only – 12" max
- C. No wide 5 wheels allowed
- D. Bead locks permitted

IT IS MANDATORY THAT ALL CARS HAVE AT LEAST ONE FIVE POUND FIRE EXTINGUISHER, READY TO USE, NO EXCEPTIONS